

AQUAFOG

Depend on AquaFog® 400™ for the ultimate in quiet, reliable performance in several applications



SPECIFICATIONS:

- Fogging Capability: 0-2 GPH / 0-7 Liters per hour
- CFM: 840 @ 60Hz / 710 @ 50HZ
- Energy Consumption: .97 AMP @ 115 Volt / .36 AMP @ 230 Volt
- Noise @ 10 ft. distance: 62 db(A) @ 60Hz / 61 db(A) @ 50Hz
- Weight: 8.5 lbs / 3.8 kg
- Dimensions: Width 15" / 38 cm; Depth 12.5" / 32 cm; Height 20.5" / 52 cm
- Voltages: - 115 Volt 60Hz 1ph
- 200-225 Volt 50Hz 1ph
- 225-250 Volt 50Hz 1ph

Standard Features:

- Compact, lightweight, good-looking design made of thermo-plastic that's highly corrosion-resistant
- Hangs high overhead, out of the way, for added convenience
- Features no-clog, nozzle-free atomization head
- Adjustable fogging capabilities up to 2 US GPH, producing particles that average 35 microns in size
- Features small, built-in sump area that reuses all of its internal condensation.. no more hassles with a drainage line
- Equipped with flow control, automatic fill float assembly and water hose connection
- Can be shipped by UPS
- Delivered fully assembled, quick to install

AQUAFOG
400
Hit and mist every time.

Aquafog® 400™

- Compact & Quiet Centrifugal Fogger



Made in
U.S.A.

Aquafog® 400™ brings advanced fine-mist fogging to the small/mid size applications. Perfectly suited in a wide range of uses from growing orchids to spot cooling horses, from cooling patios to growing speciality mushrooms. If you need an abundance of misty-fog combined with mild air propulsion Aquafog 400 is the ticket. Compact, lightweight and easy to install these stand-alone units connect right to ordinary utilities and do not require a high pressure pump or air supply line. Units fill automatically and have continuous duty capability.



- Impressive 2 gallon per hour fogging capability
- One ton of evaporative cooling per hour
- Humidification applications up to 80%
- Connects to ordinary garden hose
- Lightweight, arrives ready to install

	Model Number	Fog Output	Electrical Rating
Domestic Voltage	XE-400	2 GPH Fogger	115V 60Hz
Foreign Voltages	XE-400-50L	7 Liters Fogger	200-225V 50Hz
	XE-400-50H	7 Liters Fogger	225-250V 50Hz

Aquafog 400 Accessories:



Jaybird Humidistat

This pre-wired humidistat in an ideal means of control for the Aquafog 400 in applications requiring 80% or less relative humidity. It incorporates a fast-acting man-made sensing element with easy access control dial.

Part No. XE-36* 110-250 Voltage range 50/60Hz

*This item is available in bulk pricing, contact Manufacturer for details



Thermostat Control

If your primary interest is indoor evaporative cooling, this pre-wired control is what you may need to automate your Aquafog 400.

- Watertight Nema 4X enclosure
- 2° F +/- temperature differential

Part No. THA-120 110-250 Voltage range 50/60Hz



Mini 360° Oscillator

Great for evaporative cooling applications, this oscillator will provide a dwell-free sweeping movement for the Aquafog 400. Includes a plug adaptor

- (6) Settings from 60 to 360°
- Separate 12' power supply Cord

Part No. XE-mini-360 115V 50/60Hz.

Part No. XE-mini-361 230V 50/60Hz.



Cycle Timer Control

If you want to maintain high humidity environments above 80% then this pre-wired control is what you may need to automate your Aquafog 400.

- Watertight Nema 4X enclosure
- 4 different cycle ranges 5 to 60

Part No. CTA-120 110-250 Voltage range 50/60Hz